

Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom



*Product image may differ from actual product

Harness the power of focus

Keep presentations engaging with the Poly Studio E60 smart MPTZ optical zoom camera. The main presenter is always in frame, and every person in the room is shown with exceptional accuracy, even at the far end. With every detail captured, presentations are easier to follow.

Zoom in on all the details

Keep your hybrid teams engaged with a 12x optical zoom that offers crisp, sharp and clearer images even if you zoom in to the back of the room.

Distractions out. Engagement in

The Poly Studio E60 smart optical zoom camera harnesses AI-driven tracking and framing modes to make sure the focus stays on the all-important action.

A simplified setup and easy to use

Flexible connections and compatibility with top conferencing platforms keeps you focused on your presentation.

Featuring

Keep the focus right where it belongs

With a 12x optical zoom, the Poly Studio E60 smart MPTZ optical zoom camera can zero in on every detail and pick up content with amazing clarity.

Keep the presenter center-stage

Poly DirectorAI presenter tracking keeps the focus automatically on the main speaker, even if they're moving around the room.

Catch every detail in 4K

The ultra-HD imaging system and 4K sensors deliver razor-sharp images for a visual experience that makes virtual attendees feel more included.

In frame. In focus. Engaged

With Poly DirectorAI group framing, everyone's in-frame. Smart group framing removes excess space giving everyone more room to stand out.

No elaborate or complex set up

With an IT-friendly setup, the Poly Studio E60 MPTZ smart optical zoom camera supports flexible connections for easy collaboration.

Works with your platform of choice

The Poly Studio E60 smart MPTZ optical zoom camera is optimized and certified to work with top virtual meeting providers.

Sustainability in action

Making IT's job a little easier

Poly Lens¹, remote device management, gives you better visibility into workspaces across the entire organization. IT professionals can remotely monitor and troubleshoot Poly devices as well as streamline applying bulk software and policies.



Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom



*Product image may differ from actual product

Specifications

Compatibility

Compatible operating systems: Android; Windows

Appearance

Product colour: Black

Cable length: 6.56 ft

Camera

Camera features: Motorized pan ($\pm 170^\circ$), tilt ($\pm 30^\circ$) and zoom (MPTZ)

Camera resolution: 2160p, 4K UHD (3840 x 2160)

Diagonal field of view (dFoV): 78.1° (PTZ camera)

Horizontal field of view (hFoV): 71° (PTZ camera); 107° (panoramic camera)

Focus type: Auto focus

Total Camera Megapixels: 2 x 8 MP

Zoom capability: 12x optical

Camera type: Dual-lens

Sensor size: 1/2.8 inch CMOS sensor

Lens privacy capabilities: Attachable; Face away

Camera range: Up to 32.8 ft

Smart camera technology: Group framing; Presenter tracking; Poly DirectorAI

Video

People video resolution: 4K, 30 fps (TX and RX) from 2048 Kbps

Content video resolution (input): UHD (3840 x 2160)

Content video resolution (output): UHD (3840 x 2160)

Video frame rate: 30 fps (up to 4K resolution)

Connectivity and communications

External I/O ports:

1 USB-B; 1 RJ-45 (10/100/1000 Mbps) Ethernet interface (supporting PoE+ power supply); AC/DC power jack^{2,3}

Interoperability:

Google Meet, Microsoft Teams, Zoom certified⁵

Audio

Microphone type: Two-element beamforming microphone array⁶

Power supply

Power supply type: External

Power features: AC/DC 12 V

Power over Ethernet (PoE+) injector¹

Certifications

Certified collaboration software: Google Meet; Tencent; Microsoft Teams; Zoom

Environmental

Operating temperature range: 32 to 104 °F

Non-operating temperature: -40 to 70 °C 40 to 158 °F



Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom

Specifications

Management software

Poly Lens

Security

Standard Kensington lock slot

Network

Network capabilities: 1 10/100/1000 Mbps Ethernet supporting POE+/PSE

Weight and dimensions

Weight: 3.96 lb

Product dimensions: 7.87 x 5.9 x 6.49 in

Package weight: 8.8 lb

Package dimensions: 11.6 x 9.65 x 10.4 in

Logistic information

Master carton quantity: 20

Master carton dimension: 40.55 x 48.42 x 57.87 in

Master carton weight: 83.33 lb

Cartons per layer: 4

Layers per pallet: 5

Cartons per pallet: 20

Products per layer: 16

Products per pallet: 80

Pallet weight: 833.34 lb

Additional information

UPC number: 198122304387

Product number: 9W1A6AA

Product name: Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom

Warranty

Poly standard one-year limited warranty

Country of origin

China(AB2); Laos(AC3)

What is in the box

Ethernet cable (5 m)

Wall mount kit

Quick start guide

Warranty card

Poly Studio E60

USB-B to USB Type-A cable (2 m)

IR remote control



Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom

Accessories and services (not included)

Poly Video IEC Power Cord	Product number: 874T5AA
Poly EagleEye IV USB Camera Mounting Kit	Product number: 93S75AA
Poly Studio E60 Ceiling Mount	Product number: 9W1A8AA
Poly Studio E60 Power Accessory	Product number: 9W1A9AA

Footnotes

Messaging Footnotes

¹ Poly Lens software capabilities are limited to Poly devices and select HP cameras. For the most up to date list of supported devices you may check the support list here: <https://info.lens.poly.com/docs/begin/supported-devices>.

Technical Specifications Footnotes

- ¹ Sold separately.
- ² It connects over IP only with Poly Studio G62 and Poly G7500.
- ³ IP connection supports up to 1080p.
- ⁴ Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.
- ⁵ Compatibility with native applications and meeting services is limited by each 3rd party service's own terms and certification conditions; consult each service provider's terms as needed.
- ⁶ The microphone is designed to enable speaker tracking and it will not capture or store personal conversations and recordings.

